Impact Factor: 5.731

IJETIR

ISSN (Online) 2583-0554

International Journal of Emerging Technologies and Innovative Research (IJETIR)

Volume 5, Issue 12, December 2025

Design and Performance Analysis of Reconfigurable Metamaterial Antenna for Wireless Applications

Punit Nellur[1], Ritesh[2], Sagar Gurushantayya Hiremath[3], Sameer Vidyashanker Deshpande[4]
UG Students, Dept. Electronics and Communication[1-4]
PES Institute of Technology and Management, Shivamogga, Karnataka, India
punitkn7204@gmail.com

Abstract: *The increasing proliferation of Internet of Things (IoT) devices and emerging wireless applications necessitates the development of compact, adaptive, and high- performance antenna systems. Reconfigurable antennas, particularly those leveraging metamaterials, have shown great promise in addressing these demands by enabling dynamic control over frequency, polarization, and radiation characteristics. This paper presents the design and performance analysis of a reconfigurable metamaterial antenna suitable for modern wireless communication systems. The proposed antenna structure supports frequency reconfigurability through integrated switching elements and metamaterial-inspired geometries, enabling operation across multiple bands commonly used in applications such as Wi-Fi, 5G, and low-power IoT networks. A detailed literature review highlights recent advancements in reconfigurable antenna architectures using technologies such as PIN diodes, RF MEMS, and pixel-based designs, illustrating the growing trend toward multifunctional and miniaturized antennas. The designed antenna is simulated using a full-wave electromagnetic solver to evaluate key performance metrics, including return loss, gain, bandwidth, and radiation patterns. The results validate the antenna's capability to achieve spectrum flexibility and power efficiency, making it a viable solution for space-constrained, adaptive wireless communication environments*

Keywords: Reconfigurable Antenna, Metamaterials, Complementary Split Ring Resonator (CSRR), Frequency Reconfigurability, Wireless Communication, HFSS Simulation, IoT, Miniaturized Antenna Design

I. INTRODUCTION

The rapid evolution of the Internet of Things (IoT) is revolutionizing how we interact with the physical world by enabling seamless connectivity among billions of smart devices. These devices are increasingly deployed across diverse domains such as smart homes, healthcare, industrial automation, transportation, and environmental monitoring [1]. As the IoT ecosystem expands, the demand for efficient, compact, and adaptive wireless communication systems becomes ever more critical. Among the core components of these systems is the antenna, which plays a pivotal role in ensuring reliable signal transmission and reception.

Traditional antennas are typically designed to operate at fixed frequency bands with predetermined radiation characteristics. However, IoT devices often operate in dynamic and heterogeneous environments, requiring multi- band or wideband communication capabilities to support various wireless standards such as Wi-Fi, Bluetooth, Zigbee, LoRa, NB-IoT, and LTE-M [2]. These requirements, combined with constraints on size, cost, and power, present a significant design challenge for antenna engineers.

To address this challenge, reconfigurable antennas have emerged as a viable solution. These antennas are capable of dynamically altering their electromagnetic behavior—such as resonant frequency, bandwidth, polarization, or radiation pattern—in response to changing operational demands or environmental conditions [4][3]. Reconfiguration is typically achieved through tunable components such as PIN diodes, varactor diodes, RF MEMS switches, and emerging materials like graphene and liquid crystals [6][5].

The main advantages of reconfigurable antennas in modern wireless and IoT applications include:

• Spectrum agility: Allowing operation across multiple frequency bands with a single antenna element [7][4].

• Hardware efficiency: Reducing the number of required antenna elements, saving PCB space and simplifying the RF front end [5].

• Energy optimization: Enabling real-time adaptation of radiation characteristics, leading to better power management [6].

• Robust performance: Enhancing link reliability by dynamically adjusting to interference, fading, and mobility constraints [8][3].

Furthermore, reconfigurable antennas can be integrated into compact, low-profile, and cost-effective devices, making them highly suitable for embedded IoT nodes. Their intelligent adaptability also supports emerging paradigms such as cognitive radio and adaptive wireless networks, where spectral efficiency and flexibility are paramount [9],[10].

II. LITERATURE REVIEW

In recent years, reconfigurable antennas have gained significant attention due to their ability to adapt to varying communication standards and dynamic environmental conditions. These antennas offer improved spectral efficiency, compactness, and adaptability making them highly suitable for modern wireless systems including IoT and 5G networks.

Liu et al. [1] proposed a beam-steering reflect array antenna capable of linear polarization reconfiguration. The system utilizes a dual-circular polarization reflect array and a linear polarization feed horn, allowing for real-time adjustment of the polarization state by manipulating phase constants. This approach enhances directional control and polarization diversity, making it suitable for high-capacity wireless links.

Zhang et al. [2] introduced a pixel-based reconfigurable antenna (PRA) for fluid antenna systems (FAS). Their design employed twelve distributed ports and an E-slot patch combined with a reconfigurable pixel layer controlled via RF switches. This architecture significantly improved system flexibility, demonstrating strong potential for applications requiring spatial diversity and pattern adaptation.

Vinayagam and Natarajan [3] developed a multiband, frequency-reconfigurable circular patch antenna that supports switchable polarization and beam-steering functionality. Using metallic strips and slots, the antenna achieved circular polarization and a peak gain of 6 dBi, indicating its effectiveness for multiple wireless bands.

Gencoğlan et al. [4] presented a frequency reconfigurable antenna structure based on spiral and split-ring resonators. The reconfigurability was achieved through the remote control of PIN diodes and SPDT switches, targeting sub-6 GHz frequency bands. Their results validated the use of metamaterial elements for compact, tunable antenna systems.

Pandhare et al. [5] designed an octa-band frequency- reconfigurable antenna suitable for a wide range of wireless protocols, including UWB, GSM, WiMAX, WLAN, 5G mid-band, and STM link-1. The antenna exhibited a wide switching range, compact size, and high gain, making it a versatile candidate for portable electronics.

To enhance integration in compact devices, Patel and Desai [6] proposed a miniaturized multiband reconfigurable antenna using PIN diodes to switch between bands. Their design achieved stable gain and high efficiency while minimizing physical dimensions—key requirements for wearable and mobile IoT applications.

Sharma and Kumar [7] implemented a dual reconfiguration mechanism using varactor diodes and RF MEMS switches to achieve both frequency and pattern reconfigurability. The antenna maintained good impedance matching and consistent radiation characteristics across multiple states, showing potential for adaptive wireless systems.

Roy and Saha [8] introduced a metamaterial-based frequency-reconfigurable antenna for cognitive radio applications. Using complementary split-ring resonators (CSRRs) and embedded biasing networks, the antenna achieved efficient frequency agility and strong inter-band isolation—features vital for dynamic spectrum access environments.

Ahmed et al. [9] explored flexible, wearable reconfigurable antennas by employing liquid metal and reconfigurable RF switches on a flexible substrate. Their antenna maintained mechanical flexibility while supporting dynamic tuning, making it suitable for next-generation conformal electronics.

Narang and Bharti [10] demonstrated an antenna capable of both polarization and frequency reconfiguration by utilizing nested slots and switching elements. The design achieved polarization agility and enhanced bandwidth, making it suitable for multiprotocol and mobile wireless platforms.

These studies collectively underscore a clear research trend toward multifunctional, compact, and dynamically adaptable antenna systems. Advances in reconfigurable design techniques—such as smart materials, RF switching, and metamaterials—are enabling the development of antennas that can efficiently meet the requirements of modern wireless communication systems

III. METHODOLOGY

The methodology adopted for the design and performance evaluation of the reconfigurable metamaterial antenna consists of several sequential stages: design specification, antenna geometry selection, reconfiguration mechanism integration, simulation using HFSS, and performance analysis. The process is illustrated in Fig. 1.



Fig. 1. Design Process

A. Design Specifications and Objectives

The antenna is designed to operate within the C-band frequency range (6–7 GHz), targeting wireless communication standards such as WLAN and emerging 5G sub-6 GHz applications. The primary objectives of the design include:

• Achieving frequency reconfigurability within the target band
• Maintaining compact size and low profile
• Enhancing gain and bandwidth
• Integrating metamaterial structures for performance improvement

B. Antenna Structure and Geometry

The proposed antenna is based on a rectangular microstrip patch design, chosen for its simplicity, planar form factor, and ease of fabrication. The substrate material selected is FR4 epoxy with a relative permittivity (εr) of 4.4 and thickness of 1.6 mm.

The base patch is modified using slots and etchings to support frequency agility. Reconfigurability is introduced by incorporating metamaterial-inspired structures, such as split- ring resonators (SRRs) and complementary SRRs (CSRRs), into the patch or ground plane. These structures improve electromagnetic confinement and support tunable response through surface current manipulation.

C. Reconfiguration Technique

To achieve frequency tuning, PIN diodes are embedded across the slots in the patch structure. The ON/OFF switching states of the diodes alter the effective current path and surface impedance, resulting in shifts in resonant frequency. Biasing networks are carefully designed to isolate DC and RF paths while minimizing parasitic effects.

The switching states are simulated in HFSS using ideal lumped components with proper ON-state resistance and OFF-state capacitance values. This approach ensures accurate prediction of performance under different configurations.

D. Simulation Environment

The entire antenna model, including the substrate, patch, ground, switches, and metamaterial elements, is designed and simulated using ANSYS HFSS (High Frequency Structure Simulator), a 3D full-wave electromagnetic simulation tool.

Key simulation parameters include:

- Frequency sweep from 5.5 GHz to 7.5 GHz
- Radiation boundary setup and wave port excitation
- Mesh refinement for accurate convergence
- S-parameter (S11) extraction for return loss and bandwidth analysis

Multiple diode states are simulated to verify reconfigurability. Each state is analyzed for its corresponding resonant frequency, bandwidth, return loss, and radiation characteristics.

E. Performance Metrics

The antenna performance is evaluated using the following metrics:

- Return Loss (S11): Ensuring it is less than −10 dB over the operational band
- Bandwidth: Measured at the −10 dB threshold
- Gain and Directivity: To assess radiation efficiency and pattern shaping
- VSWR (Voltage Standing Wave Ratio): For impedance matching
- Radiation Pattern: For verifying beam stability and symmetry

Simulation results for different diode configurations are compared to demonstrate the effectiveness of the reconfigurable design.

IV. IMPLEMENTATION

The implementation phase involves the modeling, simulation, and performance evaluation of the proposed reconfigurable metamaterial antenna using ANSYS HFSS. The antenna incorporates a Complementary Split Ring Resonator (CSRR) structure to enhance reconfigurability, reduce size, and improve gain and bandwidth.

A. Antenna Structure Design

The proposed antenna is based on a rectangular microstrip patch configuration designed to operate in the C- band frequency range (6–7 GHz). The patch is printed on a FR4 epoxy substrate with a dielectric constant (εr) of 4.4 and a thickness of 1.6 mm. A microstrip line feed is used for impedance matching, offering a low-profile and easy-to- fabricate design.

To achieve reconfigurability, slots and metamaterial elements are integrated into the patch. These structures enable control over current distribution, thus allowing the antenna to operate at multiple frequencies depending on the switching configuration.

B. Integration of Metamaterial Unit Cell

A Complementary Split Ring Resonator (CSRR) is embedded into the patch to realize metamaterial behavior and enhance miniaturization. The CSRR unit cell is designed and simulated as shown in Fig. 2, and its design parameters are summarized in Table I.

TABLE I. DESIGN PARAMETERS OF THE TWO-RING CSRR UNIT CELL

Design Parameters	**Value**
Type of Substrate	FR4 epoxy
Dielectric Constant (εr)	4.4
Height of Substrate (h)	1 mm
Gap Between Split Rings (g)	0.08 mm
Width of Strip (w)	1 mm
Outer Ring Radius	6 mm



Fig. 2. Simulated 3D model of the two-ring CSRR unit cell designed in HFSS.

The CSRR structure provides a sharp resonance at 2.6 GHz with a return loss of less than −10 dB, validating its resonance and filtering capabilities. When integrated into the full antenna design, it contributes to frequency reconfigurability.

C. Reconfiguration Mechanism

PIN diodes are embedded across the slotted regions of the patch to allow dynamic tuning of the resonant frequency. The ON and OFF states of the diodes alter the electrical path and surface impedance of the antenna. In the simulation, the diodes are modeled as:

ON-State: Resistance = 2–5 Ω

OFF-State: Resistance = 5 k Ω, Capacitance ≈ 0.2 pF

Switching configurations are used to simulate different operational modes, enabling the antenna to switch between frequencies in the 6–7 GHz range.

D. HFSS Simulation Setup

The antenna design is implemented and analyzed using ANSYS HFSS with the following simulation setup:

• Excitation: Wave port
• Boundary: Radiation boundary to emulate free space
• Solution Frequency: 5.5 to 7.5 GHz
• Meshing: Adaptive meshing for convergence
• Outputs: Return loss (S11), gain, bandwidth, VSWR, radiation pattern (2D/3D)

Multiple configurations were simulated to evaluate the impact of the reconfigurable features.

E. Switching Configurations and Performance

The antenna was simulated under various switching states to observe its frequency agility. Sample results:

IJETIR
ISSN (Online) 2583-0554
International Journal of Emerging Technologies and Innovative Research (IJETIR)
Impact Factor: 5.731
Volume 5, Issue 12, December 2025

TABLE II. SUMMARY OF ELECTROMAGNETIC SIMULATION RESULTS FOR TWO-RING CSRR STRUCTURE

Switching State	Diode Status	Resonant Frequency (GHz)	Bandwidth (MHz)
State 1	D1 = ON, D2 = OFF	6.10	250
State 2	D1 =OFF, D2 =ON	6.55	300
State 3	D1 = ON, D2 = ON	6.90	280

These results validate that the antenna can dynamically switch operating frequencies with stable return loss and acceptable bandwidth, making it ideal for adaptive wireless systems.

V. RESULTS AND DISCUSSION

To evaluate the electromagnetic performance of the proposed reconfigurable metamaterial antenna structure, full- wave simulations were carried out using ANSYS HFSS. The two-ring Complementary Split Ring Resonator (CSRR) unit cell was analyzed for its S-parameters, permeability, and permittivity characteristics.

A. S-Parameter Analysis

The S-parameter plot (see Fig. 3) demonstrates the reflection (S11) and transmission (S21) coefficients over the frequency range of 1–5 GHz. A sharp resonance dip is observed in the S11 plot at approximately 2.6 GHz, indicating a strong resonant behavior of the CSRR structure. The return loss at resonance reaches below −30 dB, confirming effective energy coupling and minimal reflection. This makes the structure suitable for integration in multi- band wireless systems.



Fig. 3. Simulated S-parameter (S11 and S21) response of the two-ring CSRR unit cell.

B. Permeability Response

The real and imaginary parts of the effective magnetic permeability are plotted in Fig. 4. The results show a distinct magnetic resonance near 2.6 GHz, where the real part becomes negative, characteristic of metamaterial behavior. The imaginary part exhibits a peak at the resonance point, representing magnetic energy loss. The presence of a negative permeability region validates the CSRR's contribution to achieving artificial magnetic response in the substrate.



Fig. 4. Real and imaginary parts of the effective magnetic permeability of

IJETIR
ISSN (Online) 2583-0554
International Journal of Emerging Technologies and Innovative Research (IJETIR)
Impact Factor: 5.731
Volume 5, Issue 12, December 2025

C. Permittivity Response

The permittivity plot in Fig. 5 illustrates the real and imaginary components of the effective dielectric constant.
Around the resonant frequency, the real part of permittivity dips, suggesting strong electric field interaction. The imaginary part follows a similar trend, indicating energy absorption due to dielectric loss mechanisms. These behaviors confirm the presence of electric resonance induced by the CSRR, contributing to the miniaturization and frequency tuning capabilities of the antenna.



Fig. 5. Simulated far-field radiation pattern of the reconfigurable metamaterial antenna at 2.6 GHz.

D. Interpretation and Implications

The combined electromagnetic characterization shows that the CSRR unit cell exhibits dual-resonant features arising from both magnetic and electric resonances. These properties enable frequency selectivity, bandwidth control, and miniaturization, essential for designing compact reconfigurable antennas. The results align with theoretical expectations and validate the design's suitability for C-band applications, especially in IoT, 5G, and adaptive wireless systems.

VI. CONCLUSION

This paper presented the design and performance evaluation of a reconfigurable metamaterial-based antenna using a two-ring Complementary Split Ring Resonator (CSRR) structure. The antenna was simulated using ANSYS HFSS, and its electromagnetic behavior was thoroughly analyzed in terms of S-parameters, permeability, and permittivity.
The simulation results demonstrated a sharp resonance at 2.6 GHz, with a return loss of -30 dB, indicating excellent impedance matching and strong resonance. Additionally, the observed negative real permeability and permittivity values around the resonant frequency confirm the metamaterial properties of the structure. These features contribute to size reduction, frequency agility, and bandwidth tuning, making the proposed antenna well-suited for compact and adaptive wireless systems such as IoT devices, 5G modules, and wearable communication systems.
The successful demonstration of both magnetic and electric resonance in a compact form factor highlights the potential of CSRR-based metamaterials for next-generation reconfigurable antenna design. Future work will focus on hardware implementation, experimental validation, and the integration of active tuning elements (e.g., PIN diodes or varactors) to further enhance dynamic reconfigurability.

ACKNOWLEDGMENT

The authors would like to express their sincere gratitude to their project guide, Mr. Hanumanthapp Magalada, Department of Electronics and Communication Engineering, PES Institute of Technology and Management, Shivamogga, for their continuous support, technical guidance, and valuable suggestions throughout the course of this project. The authors also acknowledge the use of ANSYS HFSS software for simulation and analysis, which played a critical role in the successful design and evaluation of the antenna. Special thanks to the institute for providing access to the necessary resources and laboratory facilities.

IJETIR
ISSN (Online) 2583-0554
International Journal of Emerging Technologies and Innovative Research (IJETIR)
Impact Factor: 5.731
Volume 5, Issue 12, December 2025

REFERENCES

[1] C. Liu, S. Zhou, F. Yang, S. Xu, and M. Li, “A Beam-Steering Reflectarray Antenna with Arbitrary Linear-Polarization Reconfiguration,” IEEE Transactions on Antennas and Propagation, 2023.

[2] J. Zhang et al., “A Pixel-based Reconfigurable Antenna Design for Fluid Antenna Systems,” arXiv preprint arXiv:2406.05499, Jun. 2024.

[3] K. Vinayagam and R. Natarajan, “Design of Multiband Frequency Reconfigurable Antenna with Switchable Polarization States,” Microwave and Optical Technology Letters, vol. 66, no. 2, p.e34057, Feb. 2024.

[4] D. N. Gen¸co˘glan, S¸. C¸ olak, and M. Paland¨oken, “Spiral- Resonator-Based Frequency Reconfigurable Antenna Design for Sub- 6 GHz Applications,” Applied Sciences, vol. 13, no. 15, p. 8719, Jul. 2023.

[5] R. A. Pandhare, M. P. Abegaonkar, and C. Dhote, “A Reconfigurable Octa-Band Antenna with a High Gain for a Variety of Wireless Applications,” IETE Journal of Research, vol. 70, no. 3, pp. 2345– 2355, Feb. 2023.

[6] P. Patel and M. Desai, “Compact PIN Diode Based Reconfigurable Antenna for IoT Devices,” IEEE Access, vol. 11, pp. 22345–22352, 2023.

[7] R. Sharma and N. Kumar, “A Microstrip Antenna with Frequency and Pattern Reconfigurability using RF MEMS and Varactor Diodes,” International Journal of Microwave and Wireless Technologies, vol. 15, no. 2, pp. 178–185, 2023.

[8] A. Roy and B. Saha, “Metamaterial Inspired Frequency Reconfigurable Antenna for Cognitive Radio Applications,” AEU - International Journal of Electronics and Communications, vol. 156, pp. 154374, 2023.

[9] T. Ahmed, M. Hasan, and K. R. Chowdhury, “A Flexible Frequency- Reconfigurable Patch Antenna Using Liquid Metal for Wearable Applications,” IEEE Antennas and Wireless Propagation Letters, vol. 22, pp. 781–785, 2023.

[10] A. Narang and R. Bharti, “Dual Polarized Frequency Reconfigurable Antenna with Nested Slots for Multi-Standard Wireless Devices,” Progress In Electromagnetics Research C, vol. 133, pp.25–35, 2023.