IJETIR
ISSN (Online) 2583-0554
Impact Factor: 5.731
International Journal of Emerging Technologies and Innovative Research (IJETIR)
Volume 5, Issue 12, December 2025

Improving CNN-Based Cattle Activity Recognition with Inertial Sensor Data Augmentation

Vanishri Sataraddi, Megha Shree K O, Mala S, Jyothi Bhat, Punarva P
Assistant Professor Computer Science and Engineering
RNSIT, Bengaluru, India
vanishrisataraddi@gmail.com, 1rn22cs090.meghashreeko@rnsit.ac.in
1rn22cs082.malas@rnsit.ac.in, 1rn23cs406.jyothimanjunathbhat@rnsit.ac.in
1rn22cs0123.punarva@rnsit.ac.in

Abstract: *Efficient cattle management plays a vital role in the agricultural sector, as it directly affects food production, the livelihood of rural communities, and the overall health of livestock. Traditional methods of managing cattle are often outdated—they tend to be time-consuming, error-prone, and inefficient, which can lead to issues like poor disease detection, inconsistent feeding, and missed vaccinations. With the rapid development of technologies such as Artificial Intelligence (AI), the Internet of Things (IoT), computer vision, and data analytics, more intelligent and automated livestock management systems are becoming available. These technologies offer smarter and more precise solutions for handling various aspects of cattle care. This paper reviews recent research from the past five years, focusing on four critical areas: accurate cattle counting, early disease prediction and prevention, efficient food and nutrition management, and timely vaccine scheduling and reminders. It explores how different technological approaches have been used to address these challenges, compares their performance, highlights notable innovations, and discusses existing limitations. The aim is to provide valuable insights for both researchers and farmers, offering a clear understanding of current advancements, ongoing challenges, and future directions in smart cattle management.*

Keywords*:* component, formatting, style, styling, insert

I. INTRODUCTION

1) Problem Statement & Motivation Cattle farming plays a big role in agriculture by providing milk, meat, and other important products. But managing large herds the old-fashioned way comes with problems. For instance, manually counting animals takes time and can be inaccurate. Spotting diseases late or feeding them inconsistently can lead to serious health issues and loss. Not keeping up with vaccination schedules can lead to outbreaks of preventable illnesses. As farms grow bigger and the demand for animal products increases, there's a clear need for smarter, tech-based solutions. Traditional methods are slow, require lots of labor, and often involve human error. New technologies offer ways to fix this by automating and improving how farmers manage their cattle.
2) Significance of the Topic Modern tools like IoT devices, AI models, image recognition systems, and cloud computing can make a huge difference in livestock management. For example:
• Cameras and RFID tags can count and identify animals without human input.
• AI can analyze health data to predict illness before it becomes serious.
• Smart feeding systems can make sure cattle get the right amount and type of food.
• Digital reminders can help farmers keep up with vaccinations, improving animal health and safety.
These technologies can boost productivity, reduce waste, improve animal care, and help farmers use their resources more wisely—especially in places where livestock is a key source of income and food.
3) Paper Overview This survey reviews major research developments in intelligent cattle management, especially in the following areas:
• Cattle Counting: Using technology like RFID, cameras, and sensors to track each animal accurately.

• Disease Monitoring: Applying AI and data tools to detect health issues early and prevent outbreaks.
• Feeding Management: Systems that ensure the right food, in the right amounts, is given to each animal.
• Vaccination Tracking: Tools that notify farmers when vaccines are due, so no doses are missed.

II. BACKGROUND AND FUNDAMENTAL CONCEPTS

Monitoring cattle behavior is crucial for optimizing livestock management, enabling farmers and researchers to detect health issues, monitor reproductive conditions, and assess stress levels in animals. Recently, wearable inertial sensors, such as accelerometers and gyroscopes, have gained significant importance as tools for gathering continuous time-series data that reflects animal movement and behavior patterns.
Inertial Measurement Units (IMUs), consisting of accelerometers and gyroscopes, collect motion-related data, providing raw signals that are analyzed to recognize activity patterns. However, extracting meaningful insights from such sensor data requires sophisticated computational models, with Convolutional Neural Networks (CNNs) proving particularly effective due to their ability to capture both spatial and temporal relationships in the data. CNNs automate the learning of feature hierarchies, thus eliminating the need for manual feature extraction.
One of the main challenges when training CNNs with sensor data is the scarcity of large, labeled datasets. This issue is mitigated using Data Augmentation, a technique that artificially enlarges the training dataset by applying transformations such as rotations, scaling, jittering, or time-warping to the existing data, thus enhancing the model's generalization ability and robustness.

III. CATTLE BEHAVIOR MONITORING

Cattle behavior monitoring is an essential aspect of modern livestock management systems. It provides valuable insights into an animal's health, welfare, and productivity, enabling early detection of diseases, monitoring reproductive cycles, and understanding stress levels. Traditional methods of observing cattle behavior are often labor-intensive, inefficient, and prone to human error. Consequently, the integration of wearable inertial sensors has become a game-changer in the field.



Fig. 1. cattle monitoring

A. Inertial Measurement Units (IMUs)

IMUs, which typically include accelerometers and gyroscopes, are compact, lightweight sensors that capture dynamic motion and orientation data. These sensors are attached to cattle to continuously monitor their movements and behavior, generating time-series data that represents various activities, such as walking, feeding, resting, and ruminating.

B. Data Representation and Challenges

While IMUs provide an invaluable source of raw data, the challenge lies in extracting useful information from these timeseries signals. The sensor data captured by IMUs is often noisy, unstructured, and lacks direct labels, making it difficult to interpret and classify cattle behavior accurately. Advanced computational models like Convolutional Neural Networks (CNNs) are particularly suited for addressing this challenge. CNNs excel at learning complex patterns from raw sensor data by applying convolutional filters that automatically detect important features at multiple levels of abstraction.

IJETIR
ISSN (Online) 2583-0554
Impact Factor: 5.731
International Journal of Emerging Technologies and Innovative Research (IJETIR)
Volume 5, Issue 12, December 2025

However, training CNNs with time-series data from IMUs is often constrained by the scarcity of large, labeled datasets. Labeling sensor data manually is time-consuming and expensive. This issue is alleviated through Data Augmentation, which creates synthetic variations of the original data through transformations such as rotation, scaling, time-warping, and jittering. These techniques help increase the diversity of the training dataset and improve model generalization.

C. Key Terminologies

• Sensor Data: The time-series data generated by accelerometers and gyroscopes attached to cattle, used for activity and behavior analysis.
• CNN (Convolutional Neural Network): A type of deep learning architecture designed to automatically learn hierarchical features from raw input data through convolutional layers.
• Data Augmentation: A set of techniques used to artificially enlarge a dataset by applying transformations such as scaling, rotation, and jittering.
• Behavior Classification: The task of categorizing different cattle behaviors, such as walking, feeding, or resting, from sensor data.



Fig. 2. IMU sensor attached to cattle

D. Fundamental Models

The key models used in cattle behavior monitoring and classification include:
• CNNs: Convolutional Neural Networks excel at processing spatial data and time-series data, learning hierarchical features that improve the classification accuracy.
• RNNs (Recurrent Neural Networks): Useful for modeling temporal dependencies in time-series data, allowing networks to recognize long-term patterns.
• Preprocessing Pipelines: Data normalization, noise reduction, and transformation techniques that prepare raw sensor data for effective model training.
In practice, combining CNNs with data augmentation significantly enhances model accuracy, especially when the available labeled data is insufficient for training deep models.

IV. CLASSIFICATION OF EXISTING RESEARCH

Research in the field of cattle behavior classification using inertial sensor data can be grouped into various categories based on methodology, application, and research approach:

A. Methodology-Based Classification

• Traditional Machine Learning Approaches: Techniques like Support Vector Machines (SVM), Random Forests (RF), and k-Nearest Neighbors (k-NN) rely on handcrafted features extracted from sensor data for behavior classification.
• Deep Learning Approaches: Models such as CNNs, RNNs, and hybrid architectures automatically extract features directly from the sensor data and typically outperform traditional methods.

B. Application-Based Classification
• Health Monitoring: Detecting abnormal behaviors that may indicate health issues in cattle.
• Activity Recognition: Categorizing cattle behaviors like walking, feeding, or resting.
• Precision Agriculture: Leveraging behavioral data for farm automation and decision support systems.

C. Research Approach-Based Classification
• Sensor-Centric: Focuses on optimizing sensor placement and hardware configuration to capture more accurate data.
• Algorithm-Centric: Prioritizes improving classification accuracy through advanced machine learning models or augmentation techniques.
• Data-Centric: Emphasizes acquiring diverse and highquality datasets for training and improving label quality.

D. Key Findings and Limitations
Research consistently shows that deep learning models, especially when enhanced with data augmentation techniques, outperform traditional machine learning approaches for behavior classification. However, the availability of labeled data remains a significant challenge, as does the variability in sensor placement and generalization across different breeds and environments. Furthermore, many studies lack standardized datasets, making it difficult to compare results across different approaches.

V. CRITICAL ANALYSIS AND DISCUSSION

A. Key Trends in Smart Farming and Cattle Management Research
Over the past decade, agriculture has progressively embraced smart farming solutions, shifting from traditional, laborintensive practices to data-driven, automated systems. A significant area of innovation lies within Precision Livestock Farming (PLF), where the convergence of IoT, AI, and embedded technologies has transformed livestock monitoring and health management.
A major trend in PLF is the use of lightweight, lowpower microcontrollers like the ESP32 and Raspberry Pi for localized processing and communication. These devices offer integrated Bluetooth and wi-Fi capabilities, making them ideal for deployment in remote and resource-constrained rural environments. Unlike conventional SCADA systems or industrial PLCs, these microcontrollers are cost-effective and easier to integrate with modular sensor networks.
In terms of disease detection, computer vision and AI-based models have become increasingly prevalent. Deep learning architectures such as Convolutional Neural Networks (CNNs) and YOLO are being employed to detect signs of diseases like mastitis, lumpy skin, and foot rot in cattle. However, these models often suffer from poor generalizability due to small and domain-specific training datasets. The integration of Gemini Vision Pro, a large multimodal AI model, offers a promising alternative by providing more flexible and scalable disease recognition capabilities, improving adaptability across breeds, lighting conditions, and camera resolutions.
Food management automation is another growing domain, with research highlighting the use of load cells, servo motors, and real-time clocks (RTCs) to automate the distribution of feed. These systems are typically enhanced by web-based dashboards, which allow farmers to receive alerts and adjust feed cycles remotely.
Finally, cloud-connected dashboards and mobile-compatible interfaces are increasingly seen as essential for real-time system control. Platforms such as Firebase, AWS IoT, and Azure IoT Hub are being employed to facilitate secure, bidirectional communication between edge devices and users.

B. Limitations and Research Gaps in Existing Systems

• Limited AI Robustness: AI disease prediction models based on narrow datasets often fail to perform accurately under varying environmental conditions. Gemini Vision Pro addresses this by leveraging broader visual-language understanding, which enhances detection accuracy in realworld settings.
• Isolated Functional Designs: Many implementations focus on solving singular issues, such as tracking or feeding, without offering a comprehensive, integrated solution. This leads to redundancy and inefficiency.
• Non-Intuitive Interfaces: A significant number of systems rely on serial output, LCD screens, or local-only access, which limits usability for farmers who require mobile and web-based access to real-time data.
• Cost-Prohibitive Solutions: Commercial products often carry high initial costs and recurring subscription fees, making them inaccessible to smallholder farmers. By contrast, systems built with open-source tools and affordable hardware like ESP32 offer better cost-efficiency
• Connectivity Constraints: GSM-based systems using modules like SIM800L often underperform in rural regions with poor network coverage. Switching to emailbased alerts via SMTP or adopting LoRa technology can improve message delivery and reliability.

C. Overview of Features in Traditional and Proposed Systems

Required Features and traditional systems:

Feature	Traditional System
Microcontroller	Arduino UNO
Disease Detection	CNN with static dataset
Cattle Counting	RFID
Food Management	timer-based
Reminders	GSM
User Interface	LCD display or serial monitor
Cost Efficiency	Medium to high

Required Features and Proposed systems:

Feature	Proposed System
Microcontroller	ESP32 with Wi-Fi + Bluetooth
Disease Detection	Gemini Vision Pro (multimodal AI)
Cattle Counting	Dual Ultrasonic Sensors
Food Management	Load Cell + RTC + Servod
Reminders	SMTP Email Alerts
User Interface	Real-Time Web Dashboard
Cost Efficiency	Low-cost with open-source tools

D. Identification of Research Gaps and Future Scope

– On-Device AI Inference: Current systems rely heavily on cloud processing. Incorporating edge AI using tools like TensorFlow Lite or Edge Impulse can enable real-time, offline analysis, enhancing privacy and reducing latency.
– Multisensory Health Monitoring: Most disease detection systems focus solely on visual data. Integrating temperature sensors, heart rate monitors, and motion detectors can provide a holistic view of cattle health and allow early detection of internal illnesses.
– Behavioral Analytics: Advanced models could analyze video streams to identify symptoms such as limping, reduced activity, or abnormal posture— offering a richer understanding of animal well-being.
– Energy Optimization: Implementing low-power modes, solar charging systems, or battery-efficient firmware will enhance the viability of continuous monitoring systems in remote areas with limited electricity access.
– Enhanced Notification Systems: Beyond email alerts, push notifications via mobile apps or voice assistant integration (Google Assistant, Alexa) could further simplify interaction for less tech-savvy users.

– Data-Driven Farm Management: Accumulated historical data can enable predictive analytics, trend identification (e.g., seasonal disease outbreaks), and personalized health recommendations—paving the way toward intelligent decision-making in livestock care.

VI. OPEN CHALLENGES AND FUTURE DIRECTIONS

A. Unresolved Issues

Despite significant improvements in cattle behavior classification using convolutional neural networks (CNNs) and data augmentation techniques, several challenges remain open. First, there is a lack of largescale, diverse datasets for cattle behavior under varied environmental and physiological conditions. Most datasets are limited in scope, with constrained recording durations and small subject pools, which limits generalizability across farms and regions. Second, the inherent complexity and similarity of behaviors—such as ruminating versus resting—make accurate labeling difficult, often resulting in noisy or ambiguous training data. Additionally, sensor misplacement and variability in cow anatomy introduce inconsistencies in inertial data, which standard augmentation methods may not fully address. Current methods, such as random rotation or recombination of time windows, do not guarantee label preservation in all cases, which could mislead the model during training.

B. Possible Research Directions

Future research should focus on building standardized, multi-source datasets that encompass a wider range of cattle breeds, behaviors, and farm conditions. The integration of multi-modal data (e.g., inertial sensors, video, environmental sensors) can enhance model robustness and context awareness. Moreover, semi-supervised and unsupervised learning techniques could be explored to reduce the dependency on labeled data, addressing the scarcity and labeling cost issues. There is also potential in advancing domain-specific generative models (such as behavior-aware GANs) that can synthesize realistic and label-consistent time series data. Finally, real-time behavior monitoring systems need to be developed and tested in live farm settings, emphasizing energy efficiency, data privacy, and user-friendly interfaces for farmers.

VII. CONCLUSION

∗ This research presents the design and implementation of a Smart Cattle Monitoring and Health Management System that integrates four critical modules—cattle counting, disease prediction, food management, and vaccination reminders—into a unified IoT and AI-based solution. Utilizing the ESP32 microcontroller, real-time sensors, servo automation, and AI powered disease detection through Gemini Vision Pro, the system aims to enhance operational efficiency and reduce manual overhead in livestock management. extensive testing, the system has demonstrated high accuracy in counting cattle movements, maintaining food levels based on real-time weight measurements, and sending automated vaccination alerts via email. Moreover, the ability to identify common cattle diseases from images using advanced visual language models adds an intelligent layer to conventional disease detection approaches.

∗ A key insight from this project is the impact of modular IoT and AI integration in creating scalable, low-cost, and efficient livestock management systems, particularly for small and medium-scale farms. The successful implementation of a web-based dashboard for monitoring and control further validates the role of user friendly interfaces in real-time decision making..

∗ Despite its capabilities, the system reveals areas for further research, including on-device AI inference, multi-sensor fusion for more accurate diagnostics, and offline operation for rural deployment. Future work could also explore predictive analytics, such as forecasting outbreaks or health degradation using long-term data patterns.

∗ In conclusion, this work contributes to the growing body of smart agriculture research and demonstrates how emerging technologies like ESP32 and generative AI can be leveraged to build intelligent, real-time, and autonomous cattle monitoring solutions. Continued research in this domain will be essential to address the challenges of scalability, reliability, and accessibility in future agricultural automation systems.

REFERENCES

[1] M. Stangaferro, R. Wijma, L. Caixeta, M. Al-Abri, and J. Giordano, “Use of rumination and activity monitoring for the identification of dairy cows with health disorders: Part III—Metritis,” J. Dairy Sci., vol. 99, no. 9, pp. 7422–7433, 2016.

[2] B. Sharma and D. Koundal, “Cattle health monitoring system using wireless sensor network: A survey from innovation perspective,” IET Wireless Sens. Syst., vol. 8, no. 4, pp. 143–151, 2018.

[3] P. Sepu´lveda-Varas, K. L. Proudfoot, D. M. Weary, and M. A. von Keyserlingk, “Changes in behaviour of dairy cows with clinical mastitis,” Appl. Animal Behav. Sci., vol. 175, pp. 8–13, 2016.

[4] V. Nguyen et al., “Wireless interrogation of small animal phantoms with a miniature implantded UHF RFID tag”, Proc. Of 2017 IRRR CAMA, Tsukuba, Japan, 2017.

[5] D. N. Tran, T. N. Nguyen, P. C. P. Khanh, and D. T. Tran, ”An IoTbased design using accelerometers in animal behavior recognition systems,” IEEE Sensors Journal, vol. 22, no. 18, pp. 17515-17528, 2021.

[6] B. Achour, M. Belkadi, R. Aoudjit, and M. Laghrouche, ”Unsupervised automated monitoring of dairy cows’ behavior based on Inertial Measurement Unit attached to their back,” Computers and Electronics in Agriculture, vol. 167, p. 105068, 2019

[7] Agarwal et al., ”WPAN based cattle health monitoring with labview as A data logger,” Int. j. future gener. commun. netw., vol. 9, no. 6, pp. 275-284, 2016

[8] Zhang Wenda, Xu Yuelei, Ni Jiacheng, et al. Image target recognition algorithm based on multi-scale block convolutional neural network [J]. Computer Applications, vol.036, no.004, pp.1033-1038, 2016.

[9] Y. Qiao, M. Truman, and S. Sukkarieh, “Cattle segmentation and contour extraction based on mask rcnn for precision livestock farming,” Computers and Electronics in Agriculture, vol. 165, p. 104958, 2019.

[10] D.-N. Tran, T. N. Nguyen, P. C. P. Khanh, and D.-T. Tran, “An IoT-based design using accelerometers in animal behavior recognition systems,” IEEE Sensors J., vol. 22, no. 18, pp. 17515–17528, Sep. 2022.

[11] C. Li et al., “A data augmentation method for cow behavior estimation systems using 3-axis acceleration data and neural network technology,” IEICE Trans. Fundamentals Electron. Commun. Comput. Sci., vol. 105, no. 4, pp. 655–663, 2022.

[12] R. Doyle and J. Moran, Cow Talk: Understanding Dairy Cow Behaviour to Improve Their Welfare on Asian Farms. Collingwood, VIC, Australia: CSIRO, 2015.

[13] Y. Peng et al., “Classification of multiple cattle behavior patterns using a recurrent neural network with long short-term memory and inertial measurement units,” Comput. Electron. Agriculture, vol. 157, pp. 247–253, 2019.

[14] K. Chen, D. Zhang, L. Yao, B. Guo, Z. Yu, and Y. Liu, “Deep learning for sensorbased human activity recognition: Overview, challenges, and opportunities,” ACM Comput. Surv., vol. 54, no. 4, pp. 1–40, 2021.

[15] Z. Weng, F. Meng, S. Liu, Y. Zhang, Z. Zheng, and C. Gong, “Cattle face recognition based on a Two-Branch convolutional neural network,” Comput. Electron. Agric., vol. 196, no. 106871, 2022.

[16] Kasfi, K.T.; Hellicar, A.; Rahman, A. Convolutional Neural Network for Time Series Cattle Behaviour Classification. In Proceedings of the Workshop on Time Series Analytics and Applications—TSAA ’16, Hobart, Tasmania, 5 December 2016; ACM Press:
New York, NY, USA, 2016

[17] Benaissa, S.; Tuyttens, F.A.; Plets, D.; Cattrysse, H.; Martens, L.; Vandaele, L.; Joseph, W.; Sonck, B. Classification of ingestiverelated cow behaviours using RumiWatch halter and neck-mounted accelerometers. Appl. Anim. Behav. Sci. 2019

[18] H. W. Neave, D. M. Weary, and M. A. G. von Keyserlingk, “Review: Individual variability in feeding behaviour of domesticated ruminants,” Animal, vol. 12, pp. 419–430, 2018.

[19] A. Le Guennec, S. Malinowski, and R. Tavenard, “Data augmentation for time series classification using convolutional neural networks,” in Proc. ECML/PKDD Workshop Adv. Analytics Learn. Temporal Data, 2016.

[20] C. Shorten and T. M. Khoshgoftaar, “A survey on image data augmentation for deep learning,” Journal of Big Data, vol. 6, no. 1, p. 60, 2019.

[21] M. Rony, D. Barai, Riad and M. Z. Hasan, ”Automated Foot and Mouth Disease Classification Using Transfer Learning-Based Deep Convolutional Neural Network,” 2021 12th International Conference on Computing Communication and Networking Technologies (ICCCNT), Kharagpur, India, 2021

[22]] M. D. Bah, A. Hafiane, and R. Canals, “Deep learning with unsupervised data labeling for weed detection in line crops in uav images,” Remote sensing, vol. 10, no. 11, p. 1690, 2018.

[23]] M. D. Bah, A. Hafiane, and R. Canals, “Deep learning with unsupervised data labeling for weed detection in line crops in uav images,” Remote sensing, vol. 10, no. 11, p. 1690, 2018.

[24] Y. Chen, Y. Li, T. Kong, L. Qi, R. Chu, L. Li, and J. Jia, “Scale-aware automatic augmentation for object detection,” in Proc. IEEE/CVF Conf. Comput. Vis. Pattern Recognit. (CVPR), Jun. 2021

[25] A. Ahmadi et al., “Toward automatic activity classification and movement assessment during a sports training session,” IEEE Internet Things J., vol. 2, no. 1, pp. 23–32, Feb. 2015